



MTZ72-3VI

Reciprocating compressor, MTZ72HN3BVE

Refrigerants: R404A; R407C; R452A; R407A; R134a; R454C; R407F; R513A; R448A; R454A; R455A; R449A, Segment usage: Refrigeration MT, Compressor power supply [V]: 200-230/3/60, Packing format: Single pack

PRODUCT DETAILS

I RODUCT DETAILS	
Gross weight	44.5 Kg
Net weight	42 Kg
Volume	61.54 Liter
EAN	5702428887953
Approval	CE
	UL
	UKCA
Brand technique	Reciprocating compressor
Capacity control	Fixed speed
China RoHS compliance	Out of scope
Colour	Blue
Compressor power supply [V]	200-230/3/60
Configuration code	Single
Connection type	Rotolock
Cylinder	2
Description	MTZ072-3
Diameter [mm]	288 mm
Discharge connection height [mm]	74 mm
Discharge connection pipe size [in]	3/4 in
Discharge connection size [in]	1 1/4 in
Drawing number	8502012g
Economizer	No
EU RoHS compliance	Yes with exemptions
EU RoHS exemption clause	6(a), 6(a)-l, 7(a), 7(c)-l, 8(b), 9(b)
Factory HP [bar]	25 bar
Factory LP [bar]	25 bar
Family	MTZ
Fitting remark	(shipped with rotolock version only)
Fitting sleeve	ODF
Fitting standard	Rotolock
Frequency [Hz]	60
Gauge port HP	None
Gauge port LP	Schrader
Glass mounting	Threaded
Glass torque [Nm]	50 N-m
GP LP torque [Nm]	15 N-m
High Side TS Max	150 ℃
High Side TS Min	-35 °C



PRODUCT DETAILS	
High Side Volume	0.6 L
High value of nominal voltage at	230 V
60Hz [V]	
High value of voltage range at 60Hz	253 V
[V]	
In scope of WEEE and contain	No
batteries	
IP protection class	IP55 (with cable gland)
Low Side TS Max	50 °C
Low Side TS Min	-35 °C
Low Side Volume	16.5 L
Low value of nominal voltage at	200 V
60Hz [V]	
Low value of voltage range at 60Hz	180 V
[V]	
LRA	135 A
Max pressure (PS) - high side	29.4 bar
Max pressure (PS) - low side	22.6 bar
MCC	30 A
Model number	MTZ72HN3BVE
	Internal overload protector
Mounting torque [Nm]	15 N-m
Network power supply [V/Ph/Hz]	208-230/3/60
Number of starts per hour [Max]	12
Oil charge [L]	1.8 L
Oil equalization	3/8" flare SAE
Oil equalization torque [Nm]	30 N-m
Oil reference	175PZ
Packaging height [mm]	455 mm
Packaging length [mm]	395 mm
Packaging weight [Kg]	41 kg
Packaging weight [trg]	365 mm
Packing format	Single pack
	1
Packing quantity	3
Power connections	Spade
Product group	Hermetic compressors
	Reciprocating compressor MTZ
Product Name Description REACH Candidate List substances	
Refrigerant charge [kg] [Max]	Lead (CAS no. 7439-92-1) 5 kg
Refrigerants	R134a R404A
	R407A
	R407C
	R407F
	R448A
	R449A
	R452A
	R513A
	R454A
	R454C
	R455A
Rotational speed at 60Hz [rpm]	3500 rpm



PRODUCT [DETAILS
-----------	---------

SCIP dossier no.	9b3fb119-9852-486a-92dd-53aa9c96fd3b
Segment usage	Refrigeration MT
Shipped fittings	Suction and discharge solder sleeves,
	rotolock nuts and gaskets
Shipped instructions	Installation instructions
Shipped mounting	Mounting kit with grommets, bolts,
	nuts, sleeves and washers
Shipped oil	Initial oil charge
Suction connection height [mm]	265 mm
Suction connection material	-
Suction connection pipe size [in]	7/8 in
Suction connection size [in]	1 3/4 in
Swept volume [cm3]	120.94 cm ³
Technology	Reciprocating
Test dif [bar] [Max]	30 bar
Test HP [bar] [Max]	30 bar
Test LP [bar] [Max]	25 bar
Torque earth [Nm]	3 N-m
Torque power [Nm]	3 N-m
Total height [mm]	413 mm
Туре	MTZ072
UK RoHS compliance	Out of scope
Winding resistance for three-	0.56 Ohm
phase compressors with identical	
windings [Ohm]	

For Documents, Software, Visuals and more information, please use this link to visit the product page on Danfoss Product Store 🖸

Accessories



120Z0763 🗷

Mounting, Compressor kitMounting kit 2 cylinder



8156009 🗷

Connector, Gasket

Gasket set, 1", 1-1/4", 1-3/4", OSG gaskets black and white



8156134 🗷

Electrical component, Terminal box

Service kit for terminal box 80 x 96 mm, including 1 cover, 1 clamp



120Z0576 🗷

Acoustic hood, Reciprocating

Acoustic hood for two-cylinder compressor

For more information, please use this link to visit the product page on Danfoss Product Store 🗷



Accessories



7750009 🗷

Electrical component, Discharge thermostat kit

Discharge thermostat kit



8153008 🗷

Connector, Solder sleeve

Solder sleeve, P04 (1-1/4" rotolock, 3/4" ODF)



8156132 🗷

Connector, Gasket

Gasket, 1-3/4"



8156131 🗷

Connector, Gasket

Gasket, 1-1/4"



8153013 🗷

Connector, Solder sleeve

Solder sleeve, P07 (1-3/4" rotolock, 7/8" ODF)

Spare Parts



7703006 🗷

Connector, Valve set

Valve set, V07 (1-3/4"~7/8"), V04 (1-1/4"~3/4")



8156019 🗷

Connector, Sight glass

Oil sight glass with gaskets (black and white)



120Z0459 🗷

Crankcase heater, PTC heater

PTC heater 27W



7773109 🗹

Crankcase heater, Belt heater

Belt type crankcase heater, 65 W, 110 V

For more information, please use this link to visit the product page on Danfoss Product Store 🗷



Spare Parts



8156145 🗷

Connector, Gasket

Gasket for oil sight glass (black chloroprene)



8168032 🗷

Connector, Rotolock service valve

Rotolock valve, V07 (1-3/4" rotolock, 7/8" ODF)



120Z0639 🗷

Lubricant, 175PZ

POE lubricant, 175PZ,2.5L CAN



120Z0638 🗷

Lubricant, 175PZ

POE lubricant, 175PZ, 1-litre can



8168029 🗷

Connector, Rotolock service valve

Rotolock valve, V04 (1-1/4" rotolock, 3/4" ODF)



7773107 🗷

Crankcase heater, Belt heater

Belt type crankcase heater, 65 W, 230 V