



MTZ50-3VI 🖄

Reciprocating compressor, MTZ50HK3BVE

Refrigerants: R404A; R407C; R452A; R407A; R134a; R454C; R407F; R513A; R448A; R454A; R455A; R449A, Segment usage: Refrigeration MT, Compressor power supply [V]: 200-230/3/60, Packing format: Single pack

PRODUCT DETAILS

Gross weight	39.5 Kg
Net weight	37 Kg
Volume	61.54 Liter
EAN	5702428888103
Approval	CE
	UL
	UKCA
Brand technique	Reciprocating compressor
Capacity control	Fixed speed
China RoHS compliance	Out of scope
Colour	Blue
Compressor power supply [V]	200-230/3/60
Configuration code	Single
Connection type	Rotolock
Cylinder	2
Description	MTZ050-3
Diameter [mm]	288 mm
Discharge connection height [mm]	74 mm
Discharge connection pipe size [in]	3/4 in
Discharge connection size [in]	1 1/4 in
Drawing number	8502012g
Economizer	No
EU RoHS compliance	Yes with exemptions
EU RoHS exemption clause	6(a), 6(a)-1, 7(a), 7(c)-1, 8(b), 9(b)
Factory HP [bar]	25 bar
Factory LP [bar]	25 bar
Family	MTZ
Fitting remark	(shipped with rotolock version only)
Fitting sleeve	ODF
Fitting standard	Rotolock
Frequency [Hz]	60
Gauge port HP	None
Gauge port LP	Schrader
Glass mounting	Threaded
Glass torque [Nm]	50 N-m
GP LP torque [Nm]	15 N-m
High Side TS Max	150 ℃
High Side TS Min	-35 °C



Product Detail | Reciprocating compressor, MTZ50HK3BVE

PRODUCI DEIAILS	PRODUCT	DETAILS
-----------------	---------	---------

High Side Volume	0.6 L
High value of nominal voltage at	230 V
60Hz [V]	
High value of voltage range at 60Hz	253 V
[V]	
In scope of WEEE and contain	No
batteries	
IP protection class	IP55 (with cable gland)
Low Side TS Max	50 °C
Low Side TS Min	-35 °C
Low Side Volume	16.5 L
Low value of nominal voltage at	200 V
60Hz [V]	
Low value of voltage range at 60Hz	180 V
[V]	
LRA	115 A
Max pressure (PS) - high side	29.4 bar
Max pressure (PS) - low side	22.6 bar
мсс	25 A
Model number	MTZ50HK3BVE
Motor protection	Internal overload protector
Mounting torque [Nm]	15 N-m
Network power supply [V/Ph/Hz]	208-230/3/60
Number of starts per hour [Max]	12
Oil charge [L]	1.8 L
Oil equalization	3/8" flare SAE
Oil equalization torque [Nm]	30 N-m
Oil reference	175PZ
Packaging height [mm]	455 mm
Packaging length [mm]	395 mm
Packaging weight [Kg]	39 kg
Packaging width [mm]	365 mm
Packing format	Single pack
Packing quantity	1
Phase	3
Power connections	Spade
Product group	Hermetic compressors
Product group Product Name Description	Reciprocating compressor MTZ
REACH Candidate List substances	Lead (CAS no. 7439-92-1)
Refrigerant charge [kg] [Max]	
	5 kg
Refrigerants	R134a R404A
	R407A
	R407C
	R407F
	R448A
	R449A
	R452A
	R513A
	R454A
	R454C
	R455A
Rotational speed at 60Hz [rpm]	3500 rpm
·	·

PRODUCT DETAILS

SCIP dossier no.	9b3fb119-9852-486a-92dd-53aa9c96fd3b	
Segment usage	Refrigeration MT	
Shipped fittings	Suction and discharge solder sleeves,	
	rotolock nuts and gaskets	
Shipped instructions	Installation instructions	
Shipped mounting	Mounting kit with grommets, bolts,	
	nuts, sleeves and washers	
Shipped oil	Initial oil charge	
Suction connection height [mm]	265 mm	
Suction connection material	-	
Suction connection pipe size [in]	7/8 in	
Suction connection size [in]	1 3/4 in	
Swept volume [cm3]	85.64 cm ³	
Technology	Reciprocating	
Test dif [bar] [Max]	30 bar	
Test HP [bar] [Max]	30 bar	
Test LP [bar] [Max]	25 bar	
Torque earth [Nm]	3 N-m	
Torque power [Nm]	3 N-m	
Total height [mm]	413 mm	
Туре	MTZ050	
UK RoHS compliance	Out of scope	
Winding resistance for three-	0.74 Ohm	
phase compressors with identical		
windings [Ohm]		

For Documents, Software, Visuals and more information, please use this link to visit the product page on Danfoss Product Store 🖸

	120Z0763 ☑ Mounting, Compressor kit Mounting kit 2 cylinder
	8153008 🗠
0	Connector, Solder sleeve Solder sleeve, P04 (1-1/4" rotolock, 3/4" ODF)
	120Z0576 전
	Acoustic hood, Reciprocating Acoustic hood for two-cylinder compressor
	7750009 🖻
T. C. C.	Electrical component, Discharge thermostat kit
0	Discharge thermostat kit

alterations can be made without sub-sequential changes being necessary in specifications already agreed. All trademarks in this material are property of the respective companies. Danfoss and the Danfoss logotype are trademarks of Danfoss A/S.

All rights reserved.

Product Detail | Reciprocating compressor, MTZ50HK3BVE





-	8156131 🖻
	Connector, Gasket
	Gasket, 1-1/4"
	8153013 🛙
	Connector, Solder sleeve
	Solder sleeve, P07 (1-3/4" rotolock, 7/8" ODF)
	8156009 ⊠
	Connector, Gasket
	Gasket set, 1", 1-1/4", 1-3/4", OSG gaskets black and white
	8156132 ⊠
	Connector, Gasket
	Gasket, 1-3/4"
	8156134 🛙
	Electrical component, Terminal box
	Service kit for terminal box 80 x 96 mm, including 1 cover, 1 clamp
	Service kit for terminal box 80 x 96 mm, including 1 cover, 1 clamp
Parts	
Parts	
Parts	
Parts	120Z0638 № Lubricant, 175PZ POE lubricant, 175PZ, 1-litre can
Parts	120Z0638 ⊠ Lubricant, 175PZ
Parts	120Z0638 [2] Lubricant, 175PZ POE lubricant, 175PZ, 1-litre can 8168029 [2]
Parts	120Z0638 [2 Lubricant, 175PZ POE lubricant, 175PZ, 1-litre can 8168029 [2] Connector, Rotolock service valve
Parts	120Z0638 № Lubricant, 175PZ POE lubricant, 175PZ, 1-litre can 8168029 № Connector, Rotolock service valve Rotolock valve, V04 (1-1/4" rotolock, 3/4" ODF)
Parts	120Z0638 IP Lubricant, 175PZ POE lubricant, 175PZ, 1-litre can 8168029 IP Connector, Rotolock service valve Rotolock valve, V04 (1-1/4" rotolock, 3/4" ODF) 120Z0459 IP
Parts	120Z0638 [2] Lubricant, 175PZ POE lubricant, 175PZ, 1-litre can 8168029 [2] Connector, Rotolock service valve Rotolock valve, V04 (1-1/4" rotolock, 3/4" ODF) 120Z0459 [2] Crankcase heater, PTC heater
Parts	120Z0638 [2] Lubricant, 175PZ POE lubricant, 175PZ, 1-litre can 8168029 [2] Connector, Rotolock service valve Rotolock valve, V04 (1-1/4" rotolock, 3/4" ODF) 120Z0459 [2] Crankcase heater, PTC heater PTC heater 27W

For more information, please use this link to visit the product page on Danfoss Product Store 🗈

Product Detail | Reciprocating compressor, MTZ50HK3BVE

_

ENGINEERING TOMORROW



Spare Parts	
O	7773109 🖻 Crankcase heater, Belt heater Belt type crankcase heater, 65 W, 110 V
	7773107 🖻 Crankcase heater, Belt heater Belt type crankcase heater, 65 W, 230 V
	7703006 ⊵ Connector, Valve set Valve set, V07 (1-3/4"~7/8"), V04 (1-1/4"~3/4")
	8156019 2 Connector, Sight glass Oil sight glass with gaskets (black and white)
	8156145 ☑ Connector, Gasket Gasket for oil sight glass (black chloroprene)
No.	8168032 Connector, Rotolock service valve Rotolock valve, V07 (1-3/4" rotolock, 7/8" ODF)

For more information, please use this link to visit the product page on Danfoss Product Store 🗈