



115N0656 12

Optyma™, OP-HGZ064D40N

Segment usage: Medium Back Pressure, Refrigerant: R134a; R404A; R448A; R449A; R452A; R513A, Compressor power supply [V/Ph/Hz]: 230/1/60

PRODUCT DETAILS

Gross weight	173 kg	
Net weight	158 kg	
Applications	НВР	
	MBP	
Compressor model	MTZ064-1	
Compressor power supply [V/Ph/	230/1/60	
Hz]		
Condenser type	N8	
Description	OP-HGZ064D40N	
Electrical code	N	
Fan current @ 60Hz [A]	3.6 A	
Fan diameter [mm]	457 mm	
Fan power consumption @ 60Hz [W]	450 W	
Fan power supply [V/Ph/Hz]	230/1/60	
Model number	OP-HGZ064D40N	
No. of phases (compressor)	1	
No. of phases (fan)	1	
Number of fans	2	
Refrigerant	R134a	
	R404A	
	R448A	
	R449A	
	R452A	
	R513A	
Segment usage	Medium Back Pressure	
Technology	Reciprocating	
Туре	Optyma™	
Type designation	Condensing Units	
Version	D40	Optyma - Standard version for Brazil +
		full E-box + Housing

For Documents, Software, Visuals and more information, please use this link to visit the product page on Danfoss Product Store 🗅

Danfoss can accept no responsibility for possible errors in catalogs, brochures and other printed material. Danfoss reserves the right to alter its products without notice. This also applies to products already on order provided that such alterations can be made without sub-sequential changes being necessary in specifications already agreed. All trademarks in this material are property of the respective companies. Danfoss and the Danfoss logotype are trademarks of Danfoss A/S. All rights reserved.



Spare Parts



014L0026 2

SGP 16 I, Sight glass, FLARE, 16.00 mm, FLARE, 16.00 mm

Inlet connection type: FLARE, Inlet size [mm]: 16.00, Outlet connection type: FLARE, Outlet size [mm]: 16.00



023Z5045 🗷

Hermetic filter drier, DML, 16 cu.in., Steel

Inlet connection type: FLARE, Outlet connection type: FLARE, Core Size code: 16 cu.in.



061F6050 ¹²

Cartridge pressure switch, ACB, 26.50 bar, 18.00 bar

Higher activ. pressure [bar]: 26.50, Lower activ. pressure [bar]: 18.00, Reset function: Auto, Contact function: SPST(NC), Pressure connection type: Flare, Pressure connection size: 1/4 in, Electrical connection: Cable, Enclosure rating IP: IP65



118U6014 12

Condensing Units Accessories & Spare parts: Receiver

Receiver 18L



119-8453A 🗷

Condensing Units Accessories & Spare parts: Starting relay

Starting Relay Type 3ARR3J4A4



120Z0459 🗷

Compressors Accessories: PTC heater

PTC heater 27W



120Z0638 🗷

Compressors Accessories : 175PZPOE lubricant. 175PZ. 1-litre can



191U006410 ₺

Condensing Units Accessories & Spare parts: Miscellaneous

Suction Accumulator, ASD080H09 1 1/8 in



191U007710 🗷

Condensing Units Accessories & Spare parts : Oil Separator

Oil Separator, Hermetic OSD025H05 5/8in

For more information, please use this link to visit the product page on Danfoss Product Store 🗷

Danfoss can accept no responsibility for possible errors in catalogs, brochures and other printed material. Danfoss reserves the right to alter its products without notice. This also applies to products already on order provided that such alterations can be made without sub-sequential changes being necessary in specifications already agreed. All trademarks in this material are property of the respective companies. Danfoss and the Danfoss logotype are trademarks of Danfoss A/S. All rights reserved.



Spare Parts

Image coming

191U0645E 12

Condensing Units Accessories & Spare parts

MCHE, N8 Coil + Fan shroud



191U127767 2

Condensing Units Accessories & Spare parts: Kit housing

Housing, N8 Optyma™ Line



191U9907 🗷

Condensing Units Accessories & Spare parts: Filter

Basket Filter,35 X 38MM APC-474 1 3/4 in



6804503V04 2

Condensing Units Accessories & Spare parts : Service Valve

Rotalock valve V04 1 1/4-12R X 3/4 S



6804506V02 ¹²

Condensing Units Accessories & Spare parts: Service Valve

Rotalock valve V02 1 3/4 -12R X 1 1/8 S



6804507V10 2

Condensing Units Accessories & Spare parts: Service Valve

Rotalock valve V10 1-14R X 5/8 S



MTZ64-1VI 🗷

Reciprocating compressor, MTZ64HM1BVE

Refrigerant: R134a; R404A; R407A; R407C; R407F; R448A; R449A; R452A; R513A, Segment usage:

Refrigeration MT, Compressor power supply [V/Ph/Hz]: 208-230/1/60