

**MT22-1VI****Reciprocating compressor, MT22JC1TVE**

Refrigerants: R22, Segment usage: Refrigeration MT, Compressor power supply [V]: 208-230/1/60, Packing format: Single pack

PRODUCT DETAILS

Gross weight	24.75 Kg
Net weight	23 Kg
Volume	37.73 Liter
EAN	5702428839822
Approval	CE UL UKCA
Auxiliary winding resistance (start winding) for single-phase compressors [Ohm]	2.31
Brand technique	Reciprocating compressor
Capacity control	Fixed speed
Capacity of capacitor A	30 µF
Capacity of capacitor B	100 µF
Capacity of capacitor C	15 µF
China RoHS compliance	Out of scope
Colour	Blue
Compressor power supply [V]	208-230/1/60
Configuration code	Single
Connection type	Rotolock
Cylinder	1
Description	MT022-1
Diameter [mm]	224 mm
Discharge connection height [mm]	68 mm
Discharge connection pipe size [in]	1/2 in
Discharge connection size [in]	1 in
Drawing number	8501022e
Economizer	No
EU RoHS compliance	Yes with exemptions
EU RoHS exemption clause	6(a), 6(a)-I, 7(a), 7(c)-I, 8(b), 9(b)
Factory HP [bar]	25 bar
Factory LP [bar]	25 bar
Family	MT
Fitting remark	(shipped with rotolock version only)
Fitting sleeve	ODF
Fitting standard	Rotolock
Frequency [Hz]	60
Gauge port HP	None
Gauge port LP	Schrader

Danfoss can accept no responsibility for possible errors in catalogs, brochures and other printed material. Danfoss reserves the right to alter its products without notice. This also applies to products already on order provided that such alterations can be made without sub-sequential changes being necessary in specifications already agreed. All trademarks in this material are property of the respective companies. Danfoss and the Danfoss logotype are trademarks of Danfoss A/S. All rights reserved.

Product Detail | Reciprocating compressor, MT22JC1TVE

PRODUCT DETAILS

Glass mounting	Threaded
Glass torque [Nm]	50 N-m
GP LP torque [Nm]	15 N-m
High Side TS Max	150 °C
High Side TS Min	-35 °C
High Side Volume	0.3 L
High value of nominal voltage at 60Hz [V]	230 V
High value of voltage range at 60Hz [V]	253 V
In scope of WEEE and contain batteries	No
IP protection class	IP55 (with cable gland)
Low Side TS Max	50 °C
Low Side TS Min	-35 °C
Low Side Volume	7.5 L
Low value of nominal voltage at 60Hz [V]	208 V
Low value of voltage range at 60Hz [V]	187 V
LRA	53 A
Main winding resistance for single-phase compressors [Ohm]	1.2
Max pressure (PS) - high side	29.4 bar
Max pressure (PS) - low side	18.4 bar
MCC	17 A
Model number	MT22JC1TVE
Motor protection	Internal overload protector
Mounting torque [Nm]	15 N-m
Network power supply [V/Ph/Hz]	208-230/1/60
Number of starts per hour [Max]	12
Oil charge [L]	0.95 L
Oil equalization	3/8" flare SAE
Oil equalization torque [Nm]	30 N-m
Oil reference	160P
Packaging height [mm]	385 mm
Packaging length [mm]	330 mm
Packaging weight [Kg]	25 kg
Packaging width [mm]	295 mm
Packing format	Single pack
Packing quantity	1
Phase	1
Power connections	Spade
Product group	Hermetic compressors
Product Name Description	MT
REACH Candidate List substances	Lead (CAS no. 7439-92-1)
Refrigerant charge [kg] [Max]	2.5 kg
Refrigerants	R22
Rotational speed at 60Hz [rpm]	3500 rpm
SCIP dossier no.	5a332c1b-1d1b-4998-8115-d0929877ecb4
Segment usage	Refrigeration MT

Danfoss can accept no responsibility for possible errors in catalogs, brochures and other printed material. Danfoss reserves the right to alter its products without notice. This also applies to products already on order provided that such alterations can be made without sub-sequential changes being necessary in specifications already agreed. All trademarks in this material are property of the respective companies. Danfoss and the Danfoss logotype are trademarks of Danfoss A/S. All rights reserved.

Product Detail | Reciprocating compressor, MT22JC1TVE

PRODUCT DETAILS

Shipped fittings	Suction and discharge solder sleeves, rotolock nuts, and gaskets
Shipped instructions	Installation instructions
Shipped mounting	Mounting kit with grommets, bolts, nuts, sleeves and washers
Shipped oil	Initial oil charge
Suction connection height [mm]	263 mm
Suction connection material	-
Suction connection pipe size [in]	5/8 in
Suction connection size [in]	1 1/4 in
Swept volume [cm ³]	38.12 cm ³
Technology	Reciprocating
Test Dif [bar] [Max]	30 bar
Test HP [bar] [Max]	30 bar
Test LP [bar] [Max]	25 bar
Torque earth [Nm]	3 N-m
Torque power [Nm]	3 N-m
Total height [mm]	333 mm
Type	MT022
UK RoHS compliance	Out of scope
Viscosity [cP]	32 cP
Voltage of capacitor A [V]	440 V
Voltage of capacitor B [V]	330 V
Voltage of capacitor C [V]	440 V
Proposition 65	WARNING: Cancer and Reproductive Harm www.p65warnings.ca.gov

For Documents, Software, Visuals and more information, please use this link to visit the product page on Danfoss Product Store [🔗](#)

Accessories



8156134 [🔗](#)

Electrical component, Terminal box

Service kit for terminal box 80 x 96 mm, including 1 cover, 1 clamp



8173001 [🔗](#)

Electrical component, Start capacitor

Start capacitor 330V, 98 µF



7701035 [🔗](#)

Electrical component, Starting kit

PSC starting kit, 30 µF, 15 µF

For more information, please use this link to visit the product page on Danfoss Product Store [🔗](#)

Danfoss can accept no responsibility for possible errors in catalogs, brochures and other printed material. Danfoss reserves the right to alter its products without notice. This also applies to products already on order provided that such alterations can be made without sub-sequential changes being necessary in specifications already agreed. All trademarks in this material are property of the respective companies. Danfoss and the Danfoss logotype are trademarks of Danfoss A/S. All rights reserved.

Product Detail | Reciprocating compressor, MT22JC1TVE**Accessories****8153011** [🔗](#)**Connector, Solder Sleeve**

Solder sleeve, P09 (1-1/4" rotolock, 5/8" ODF)

**8156009** [🔗](#)**Connector, GASKET**

Gasket set, 1", 1-1/4", 1-3/4", OSG gaskets black and white

**8156130** [🔗](#)**Connector, GASKET**

Gasket, 1"

**8156131** [🔗](#)**Connector, GASKET**

Gasket, 1-1/4"

**8153007** [🔗](#)**Connector, Solder Sleeve**

Solder sleeve, P06 (1" rotolock, 1/2" ODF)

**120Z0575** [🔗](#)**Acoustic hood, Reciprocating**

Acoustic hood for one-cylinder compressor

**8156001** [🔗](#)**Mounting, Compressor kit**

Mounting kit for one and two-cylinder compressor, including 3 grommets, 3 bolts

Spare Parts**8156019** [🔗](#)**Connector, Sight glass**

Oil sight glass with gaskets (black and white)

**7701147** [🔗](#)**Electrical component, Starting kit**CSR starting kit, prewired box, 30 μ F, 15 μ F, 98 μ F**For more information, please use this link to visit the product page on Danfoss Product Store** [🔗](#)

Danfoss can accept no responsibility for possible errors in catalogs, brochures and other printed material. Danfoss reserves the right to alter its products without notice. This also applies to products already on order provided that such alterations can be made without sub-sequential changes being necessary in specifications already agreed. All trademarks in this material are property of the respective companies. Danfoss and the Danfoss logotype are trademarks of Danfoss A/S. All rights reserved.

Spare Parts



7701038 [🔗](#)
Electrical component, Starting kit
 CSR starting kit, 30 μ F, 15 μ F, 98 μ F



7754001 [🔗](#)
Lubricant, 160P
 Mineral oil, 160P, 2-litre can



7703005 [🔗](#)
Connector, Valve set
 Valve set, V09 (1-1/4"~5/8"), V06 (1"~1/2")



120Z0459 [🔗](#)
Crankcase heater, PTC heater
 PTC heater 27W, CE mark, UL



8173022 [🔗](#)
Electrical component, Relay
 Starting relay type RVA-6AMKL/3ARR3J4A4



8168031 [🔗](#)
Connector, Rotolock service valve
 Rotolock valve, V06 (1" rotolock, 1/2" ODF)



8168033 [🔗](#)
Connector, Rotolock service valve
 Rotolock valve, V09 (1-1/4" rotolock, 5/8" ODF)



8156145 [🔗](#)
Connector, GASKET
 Gasket for oil sight glass (black chloroprene)



7773106 [🔗](#)
Crankcase heater, Belt heater
 Belt type crankcase heater, 54 W, 230 V, CE mark, UL



7701035 [🔗](#)
Electrical component, Starting kit
 PSC starting kit, 30 μ F, 15 μ F

For more information, please use this link to visit the product page on Danfoss Product Store [🔗](#)

Danfoss can accept no responsibility for possible errors in catalogs, brochures and other printed material. Danfoss reserves the right to alter its products without notice. This also applies to products already on order provided that such alterations can be made without sub-sequential changes being necessary in specifications already agreed. All trademarks in this material are property of the respective companies. Danfoss and the Danfoss logotype are trademarks of Danfoss A/S. All rights reserved.